Dusted and Frosted Crystal Decorative Window Films. **The Perfect Match**

Properties	DecoTek Dusted Crystal	DecoTek Frosted Crystal
Visible Light Transmitted (film only)	94%	86%
UV protection	99%	99%
Base film thickness	2.3 mil cast PVC	3.4 mil cast PVC
Finish	Etched clear with matte finish	Sparkle frost clear with matte finish
Adhesive	Permanent pressure sensitive	Permanent pressure sensitive
Liner	Easy peel 3 mil PET	Easy peel 3 mil PET
Printability	Screen/UV Digital/UV Solvent/ Thermal Transfer	Screen/UV Digital/UV Solvent/ Thermal Transfer
Min. application temperature	55°F	55°F
Shelf life (@ 73°F, 50% RH)	2.5 years	2.5 years
Warranty: interior application exterior application	10 years 3 years	10 years 3 years

The above information is based on information provided by the supplier, and although believed to be reliable, it does not constitute a warranty.

MM-WF-xx-Dec-Fil-Cry-En-HT-14.1

Made in USA

HanitaTek Window Films 4010 La Reunion Parkway, Suite 100 | Dallas, TX 75212
T: 800-660-5559 | www.hanitatek.com | info@hanitatek.com

HanitaTek Window Films